

設定項目の一覧 English version is next page→

項目	表示	名称	範囲	単位	Monkey125 JB02	CT125 JA55	Monkey125 JB03	DAX125 JB04	CT125 JA65
1.1	SPEED WARN.	速度警告灯 (点灯)	30 ~ 199km/h (19 ~ 124MPH)	1	60	60	60	60	60
1.2	OIL	オイル交換距離	500 ~ 6000km (300 ~ 3900mile)	500(300)	1000	1000	1000	1000	1000
1.3	SPEED	速度誤差補正	80.0 ~ 120.0%	0.1	100.0	100.0	100.0	100.0	100.0
F 1.4	FRONT	フロントスプロケット	10 ~ 20T	1	15	14	14	15	14
F 1.5	REAR	リアスプロケット	30 ~ 50T	1	34	39	37	34	38
F 1.6	PULSE	速度信号数	1 ~ 40 ポイント	1	31	31	27	24	24
F 1.7	DIA	リアタイヤ直径	350 ~ 800mm	1	515	576	515	490	576

2.1	TACHO	シフトインジケータ-緑 (点灯)	3000 ~ 12750RPM	250	5500	5500	5500	5500	5500
2.2	TACHO	シフトインジケータ-赤 (点灯)	3250 ~ 13000RPM	250	7000	7000	7000	7000	7000
2.3	TACHO	シフトインジケータ-緑&赤 (点滅)	3250 ~ 13000RPM	250	7000	7000	7000	7000	7000
2.4	GAUGE	表示レンジ切り替え	10000RPM, 13000RPM	2 択	10000	10000	10000	10000	10000
F 2.5	TYPE	点火信号種類	POSI (+), NEGA (-)	2 択	POSI	POSI	POSI	POSI	POSI
F 2.6	PULSE	点火信号数	0.5, 1 回	2 択	0.5	0.5	0.5	0.5	0.5

3.1	TEMP	高温警告灯	50 ~ 180°C, (122 ~ 356°F)	5	130	145	110※	110※	110※
F 3.2		温度計プログラム種類	P-Obd, P-P1, P-P2, P-7, P-250	5 択	P-1	P-1	P-250※	P-250※	P-250※
F 3.3	UNIT	温度単位	°C, °F	2 択	°C	°C	°C	°C	°C

※別途ドレンボルト型温度センサーキット (M1209) が必要

4.1	ILL	バックライト輝度	1 ~ 5 レベル	1	5	5	5	5	5
4.2	START UP	起動画面	A, B, C	3 択	A	A	A	A	A
4.3	ABS	ABS 有無	ON, OFF	2 択	ON/OFF	ON	ON	ON	ON
F 4.4	ODO	ユーザーオド	0 ~ 99999km (0 ~ 99999mile)	1	0	0	0	0	0
F 4.5	UNIT	距離単位	km, mile	2 択	km	km	km	km	km
F 4.6	V-ADD	電圧計補正	-1.0 ~ 1.0V	0.1	0	0.8	0	0	0

F 5.1	PRI	1 次減速比	2.000 ~ 5.000	0.001	3.350	3.350	3.040	3.421	3.421
F 5.2	1 ST	変速比	1 速	0.505 ~ 5.000	0.001	2.500	2.500	2.846	2.500
F 5.3	2 ND		2 速	0.504 ~ 4.999, NON	0.001	1.550	1.550	1.777	1.550
F 5.4	3 RD		3 速	0.503 ~ 4.998, NON	0.001	1.150	1.150	1.315	1.150
F 5.5	4 TH		4 速	0.502 ~ 4.997, NON	0.001	0.923	0.923	1.034	0.923
F 5.6	5 TH		5 速	0.501 ~ 4.996, NON	0.001	NON	NON	0.843	NON
F 5.7	6 TH		6 速	0.500 ~ 4.995, NON	0.001	NON	NON	NON	NON
F 5.8	DISP RATIO	変速比表示	ON, OFF	2 択	OFF	OFF	OFF	OFF	OFF
F 5.9	CUT	カットオフ RPM	0 ~ 4000RPM	500	0	0	0	0	0

C COMPLETE 完了する

F マーク付きは" FULL ADJ モード" 内でのみ変更できる項目

F 0.0 ← 項目番号

List of Sections 日本語版は前のページ←

Display	Name	Range	Unit	Monkey125 JB02	CT125 JA55	Monkey125 JB03	DAX125 JB04	CT125 JA65
1.1	SPEED WARN.	Speed Warning	30 ~ 199km/h (19 ~ 124MPH)	1	60	60	60	60
1.2	OIL	Oil Change Milege	500 ~ 6000km (300 ~ 3900mile)	500(300)	1000	1000	1000	1000
1.3	SPEED	Speed Fine Adjustment	80.0 ~ 120.0%	0.1	100.0	100.0	100.0	100.0
F 1.4	FRONT	Front Sprocket	10 ~ 20T	1	15	14	14	15
F 1.5	REAR	Rear Sprocket	30 ~ 50T	1	34	39	37	34
F 1.6	PULSE	Number of speed signals	1 ~ 40 Points	1	31	31	27	24
F 1.7	DIA	Rear Tire Diameter	350 ~ 800mm	1	515	576	515	490

2.1	TACHO	Shift Indicator Green (lit)	3000 ~ 12750RPM	250	5500	5500	5500	5500
2.2	TACHO	Shift Indicator Red (lit)	3250 ~ 13000RPM	250	7000	7000	7000	7000
2.3	TACHO	Green & Red (Blinking)	3250 ~ 13000RPM	250	7000	7000	7000	7000
2.4	GAUGE	Display Range Switching	10000RPM, 13000RPM	2 choices	10000	10000	10000	10000
F 2.5	TYPE	Ignition Signal Type	POSI (+), NEGA (-)	2 choices	POSI	POSI	POSI	POSI
F 2.6	PULSE	Number of Ignition Signals	0.5, 1	2 choices	0.5	0.5	0.5	0.5

3.1	TEMP	High Temp Warning	50 ~ 180°C, (122 ~ 356°F)	5	130	145	110	110	110
F 3.2		Temp Program Type	P-Obd, P-P1, P-P2, P-7, P-250	3 choices	P-1	P-1	P-250	P-250	P-250
F 3.3	UNIT	Temp Unit	°C, °F	2 choices	°C	°C	°C	°C	°C

※Requires optional drain bolt type temp sensor kit (M1209)

4.1	ILL	Backlight Brightness	1 ~ 5 Level	1	5	5	5	5
4.2	START UP	Startup screen	A, B, C	3 choices	A	A	A	A
4.3	ABS	With or without ABS	ON, OFF	2 choices	ON/OFF	ON	ON	ON
F 4.4	ODO	User Odo meter	0 ~ 99999km (0 ~ 99999mile)	1	0	0	0	0
F 4.5	UNIT	Unit of length	km, mile	2 choices	km	km	km	km
F 4.6	V-ADD	Voltmeter Correction	-1.0 ~ 1.0V	0.1	0	0.8	0	0

F 5.1	PRI	Primary Reduction Ratio	2.000 ~ 5.000	0.001	3.350	3.350	3.040	3.421	3.421
F 5.2	1 ST	Gear Ratio	1st	0.505 ~ 5.000	0.001	2.500	2.500	2.846	2.500
F 5.3	2 ND		2nd	0.504 ~ 4.999, NON	0.001	1.550	1.550	1.777	1.550
F 5.4	3 RD		3rd	0.503 ~ 4.998, NON	0.001	1.150	1.150	1.315	1.150
F 5.5	4 TH		4th	0.502 ~ 4.997, NON	0.001	0.923	0.923	1.034	0.923
F 5.6	5 TH		5th	0.501 ~ 4.996, NON	0.001	NON	NON	0.843	NON
F 5.7	6 TH		6th	0.500 ~ 4.995, NON	0.001	NON	NON	NON	NON
F 5.8	DISP RATIO	Gear Ratio display	ON, OFF	2 choices	OFF	OFF	OFF	OFF	
F 5.9	CUT	Cutoff RPM	0 ~ 4000RPM	500	0	0	0	0	

C COMPLETE Complete

Items with F mark can be changed only in "FULL ADJ mode"

F 0.0 ← Section No.